

## Product Specifications

### Transparent Indoor LED Screen - SMD

Descriptions	Parameters
Pixel pitch	3.91mm(H) 7.82mm(V)
Pixels per sqm.	32,768
Brightness	5500, 3000, 1000 cd/m <sup>2</sup>
Grey Scale	14 Bits
Display refresh rate (Hz)	1920
Viewing angle	Horizontal: ≥120°; Vertical: ≥120°
Module resolution (pixels)	64 (W) x 8 (H)
Module size (mm)	250 (W) x 62.56 (H)
Cabinet resolution (pixels)	256 (W) x 128 (H)
Cabinet dimension (mm)	1000 (W) x 1000 (H)
Max. power consumption	≤700 Watt/sqm
Avg power consumption	≤300 Watt/sqm
Input voltage	AC 110 or 220 V ±10%
Cabinet net weight (kgs)	8
Cabinet Material	Aluminium Alloy
Ingress protection	IP30
Serviceability	Front / Back
Storage Temp/Humidity	-30°C to 70°C; 10%-85%RH
Operating Temp/Humidity	-20°C to 60°C; 10%-90%RH
Lifespan (typical)	≥100,000 hours
Lifespan (70% brightness)	≥50,000 hours
Certifications	CE, RoHS, FCC, ETL, CCC



Panel

