

Product Specifications

FM4 Indoor LED Screen - SMD

Descriptions	Parameters
Pixel pitch	4mm
Pixels per sqm.	62,500
Brightness	1000 cd/m ²
Grey Scale	16 Bits
Display refresh rate (Hz)	1920/2880/3840
Viewing angle	Horizontal: ≥160°; Vertical: ≥160°
Module resolution (pixels)	64 (W) x 72(H)
Module size (mm)	256 (W) x 288 (H)
Cabinet resolution (pixels)	256 (W) x 72 (H)
Cabinet dimension (mm)	1024 (W) x 288 (H) (x49mm depth)
Max. power consumption	≤450 Watt/sqm
Avg power consumption	≤150 Watt/sqm
Input voltage	AC 110 or 220 V ±10%
Cabinet net weight (kgs)	7
Cabinet Material	Aluminium Alloy
Ingress protection	IP30
Serviceability	Front / Back
Storage Temp/Humidity	-30°C to 70°C; 10%-85%RH
Operating Temp/Humidity	-20°C to 60°C; 10%-90%RH
Lifespan (typical)	≥100,000 hours
Lifespan (70% brightness)	≥50,000 hours
Certifications	CE, RoHS, FCC, ETL, CCC



Fleixble Installation, front/rear or 90° corners



Ultra Light and thin design

